

Air Induction Service

SECTION 1. IDENTIFICATION

Product Identifier	Air Induction Service
Part number	PLI-007
Product Family	Aromatic solvent blend
Recommended Use	Cleaner.
Restrictions on Use	None known.
Supplier Identifier	Performa Lubricants International, Inc., 42 Montrose Crescent, Whitby, ON, L1R 1C5, 905.668.1440 1.800.808.3062
Emergency Phone No.	CANUTEC, +1.613.996.6666, Operation hours: 24/7

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 2; Skin irritation - Category 2; Eye irritation - Category 2A; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 1

Label Elements



Danger

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical, ventilating, and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust, fume, gas, mist, vapours or spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

IF ON SKIN: Wash with plenty of water.

Product Identifier:	Air Induction Service
SDS No.:	PLI-007
Date of Preparation:	August 17, 2016

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a POISON CENTRE or doctor if you feel unwell.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use carbon dioxide or dry chemical to extinguish.

Store in a well-ventilated place. Keep container tightly closed.
Keep cool.
Store locked up.

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Toluene	108-88-3	15-40	
Xylene (mixed isomers)	1330-20-7	10-30	
Acetone	67-64-1	10-30	
Ethylbenzene	100-41-4	5-10	
Hydrotreated, heavy naphthenic distillate	64742-52-5	0.5-1.5	
Methanol	67-56-1	0.5 - 1.5	
Hydrotreated light naphthenic distillate	64742-53-6	0.5-1.5	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a Poison Centre or doctor.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Slowly dilute with 1-2 glasses of water or milk, seek medical attention.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

Product Identifier: Air Induction Service
SDS No.: PLI-007
Date of Preparation: August 17, 2016

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Small fire: carbon dioxide or dry chemical.

Unsuitable Extinguishing Media

Do not use a direct stream of water.

Specific Hazards Arising from the Product

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air.

Carbon oxides, and other unidentified organic compounds.

Special Protective Equipment and Precautions for Fire-fighters

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet. Eliminate all ignition sources. Use grounded, explosion-proof equipment.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Methods and Materials for Containment and Cleaning Up

Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal. Contaminated absorbent poses the same hazard as the spilled product.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Wash hands thoroughly after handling this material. Avoid repeated or prolonged skin contact with product or with contaminated equipment/surfaces. Do not get in eyes, on skin or on clothing.

Conditions for Safe Storage

Store in a closed container. Empty containers may contain hazardous residue. Store separately. Keep closed. Follow all precautions given on this safety data sheet. Protect from sunlight. Store at temperatures not exceeding: 40°C. Store in an area that is: well-ventilated.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH® TLV®		OSHA PEL	
	TWA	STEL [C]	TWA	Ceiling
Toluene	20 ppm A4	Not established	Not established	Not established
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	435 mg/m3	Not established
Acetone	500 ppm A4	750 ppm A4	1000 ppm	Not established
Methanol	200 ppm	250 ppm		
Ethylbenzene	20 ppm A3	Not established	100 ppm	Not established

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space

Product Identifier: Air Induction Service

SDS No.: PLI-007

Date of Preparation: August 17, 2016

or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields.

Contact lenses should not be worn, they may contribute to the severity of the injury.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

The following materials should NOT be used: natural rubber, polyvinyl chloride, neoprene rubber.

Respiratory Protection

Not normally required if product is used as directed. If the TLV is exceeded, a NIOSH -approved respirator is advised.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	liquid.
Odour	Aromatic
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting)
Initial Boiling Point/Range	Not available
Flash Point	-8 °C (method not specified)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable (liquid).
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.85 at 20 °C
Solubility	Negligible in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic)
Other Information	
VOC %	80
Flame projection	Not applicable
NFPA Classification	Combustible liquid, Class IB

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Hazardous polymerization will not occur.

Chemical Stability

Stable at ambient temperatures and pressures.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Light

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Carbon oxides. And other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Reports have associated repeated and prolonged occupational overexposure to various organic solvents with internal organ, brain and nervous system damage.

Likely Routes of Exposure

Inhalation.

Skin contact.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Toluene	7585 ppm (rat) (4-hour exposure)	5580 mg/kg (male rat)	12125 mg/kg (rabbit)
Xylene (mixed isomers)	6350 ppm (male rat) (4-hour exposure)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)
Acetone	30000 ppm (male rat) (4-hour exposure)	5800 mg/kg (female rat)	> 15800 mg/kg (rabbit)
Methanol	64000 ppm (rat) (4-hour exposure)	5628 mg/kg (rat)	15800 mg/kg
Hydrotreated, heavy naphthenic distillate	2180 mg/m ³ (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Hydrotreated light naphthenic distillate	2180 mg/m ³ (rat)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Ethylbenzene	~ 4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)

Skin Corrosion/Irritation

Moderate skin irritant.

Serious Eye Damage/Irritation

Moderate irritant.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Depression of the central nervous system, impaired vision and blindness. In some cases, there may be delayed effects on the nervous system.

High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and headache to unconsciousness.

Skin Absorption

No information was located.

Ingestion

If small amounts are swallowed not likely to cause injury. If large amounts are swallowed can cause effects as described for inhalation. Swallowing methanol may result in blindness or other eye damage and nervous system damage.

Product Identifier: Air Induction Service

SDS No.: PLI-007

Date of Preparation: August 17, 2016

Page 05 of 08

Aspiration Hazard

Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located for respiratory sensitization.

No information was located for skin sensitization.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Toluene	A4	Group 3	Not Listed	Not Listed
Xylene (mixed isomers)	A4	Group 3	Not Listed	Not Listed
Ethylbenzene	A3	Group 2B	Not Listed	Not Listed

No components are listed as carcinogens by ACGIH, IARC, NTP or OSHA.

Reproductive Toxicity

Development of Offspring

Contains a component that contains xylene, which is reported to be fetotoxic.

Toluene is fetotoxic based on animal studies.

No information was located for: Development of Offspring, Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground or into any body of water. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of in accordance with municipal, provincial/state or federal regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1993	Flammable liquid, n.o.s. (toluene, xylene)	3	II
IATA (Air)	UN1993	Flammable liquid, n.o.s. (toluene, xylene)	3	II
IMDG (Marine)	UN1993	Flammable liquid, n.o.s. (toluene, xylene)	3	II

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Emergency Response Guide No. 128 EmS F-E, S-E

Other Information

ICAO/IATA PI Y341/353/364

Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are met.

Product Identifier: Air Induction Service

SDS No.: PLI-007

Date of Preparation: August 17, 2016

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

CEPA - National Pollutant Release Inventory (NPRI)

(Toluene) Part 1A.

(Xylene (mixed isomers)) Part 1A.

(Methanol) Part 5.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol)

California Proposition 65: Not applicable.

SARA Title III - Section 302: Not applicable.

SARA Title III - Section 313. (Toluene). (Xylene (mixed isomers)). (Methanol)

Massachusetts Right To Know: Not applicable.

New Jersey Right To Know. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol)

Pennsylvania Right To Know. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol)

SECTION 16. OTHER INFORMATION

NFPA Rating **Health - 1** **Flammability - 3** **Instability - 0**

SDS Prepared By Regulatory Compliance

Phone No. 800.201.9486

Date of Preparation August 17, 2016

Key to Abbreviations ACGIH® = American Conference of Governmental Industrial Hygienists

CANUTEC = Canadian Transportation Emergency Centre

CAS = Chemical Abstract Services

CCOHS = Canadian Centre for Occupational Health & Safety

CNS = Central nervous system

GESTIS Substance Database

HSDB® = Hazardous Substances Data Bank

IARC = International Agency for Research on Cancer

ICAO = International Civil Aviation Organization

IMDG = International Maritime Dangerous Goods Code

LC = Lethal concentration

LD = Lethal dose

NFPA = National Fire Prevention Association

NTP = National Toxicology Program

OSHA = US Occupational Safety and Health Administration

PPM = Parts per million

STEL = Short term exposure limit

TDG = Transportation of Dangerous Goods Regulations (Canada)

TWA = Time weighted average

References

Material Safety Data Sheet from manufacturer.

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS).

Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault

Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and

Product Identifier: Air Induction Service

SDS No.: PLI-007

Date of Preparation: August 17, 2016

Safety (CCOHS).

ECHA - European Chemical Agency, Classification and Labelling Inventory

GESTIS Substance Database

OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

Disclaimer

The information contained herein is offered only as a guide to the use and handling of this specific material and has been prepared in good faith. It is not intended to be all-inclusive, and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein.

Product Identifier: Air Induction Service

SDS No.: PLI-007

Page 08 of 08

Date of Preparation: August 17, 2016