

Air Intake Cleaner

SECTION 1. IDENTIFICATION

Product Identifier	Air Intake Cleaner
Part number	PLI-009
Product Family	Aromatic solvent blend
Recommended Use	Cleaner.
Restrictions on Use	None known.
Supplier Identifier	Performa Lubricants International, Inc., 42 Montrose Crescent, Whitby, ON, L1R 1C5, 905.668.1440 1.800.808.3062
Emergency Phone No.	CANUTEC, +1.613.996.6666, Operation hours: 24/7

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas; Skin irritation - Category 2; Eye irritation - Category 2A; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 1

Label Elements



Danger

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing vapours, spray.
Wash hands and skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves.
Wear eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
Do NOT induce vomiting.
IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.

Product Identifier:	Air Intake Cleaner
SDS No.:	PLI-009
Date of Preparation:	August 21, 2015

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTRE or doctor if you feel unwell.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store locked up.

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Toluene	108-88-3	15-40	
Xylene (mixed isomers)	1330-20-7	10-30	
Acetone	67-64-1	10-30	
Ethylbenzene	100-41-4	5-10	
Hydrotreated, heavy naphthenic distillate	64742-52-5	0.5-1.5	
Carbon dioxide	124-38-9	1-5	
Methanol	67-56-1	0.5 - 1.5	
Hydrotreated light naphthenic distillate	64742-53-6	0.5-1.5	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a Poison Centre or doctor.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Slowly dilute with 1-2 glasses of water or milk, seek medical attention.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Product Identifier: Air Intake Cleaner

SDS No.: PLI-009

Date of Preparation: August 21, 2015

Suitable Extinguishing Media

Small fire: carbon dioxide or dry chemical.

Unsuitable Extinguishing Media

Do not use a direct stream of water.

Specific Hazards Arising from the Product

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. sprayed product will project a flame on contact with an ignition source.

containers may explode if heated.

Vapours are heavier than air. May travel a considerable distance to a source of ignition and flash back to a leak or open container.

Carbon oxides, and other unidentified organic compounds.

Special Protective Equipment and Precautions for Fire-fighters

Use extreme caution, fight fire from a safe distance or a protected location.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet. Eliminate all ignition sources. Use grounded, explosion-proof equipment.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Methods and Materials for Containment and Cleaning Up

Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal. Contaminated absorbent poses the same hazard as the spilled product.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Wash hands thoroughly after handling this material. Avoid repeated or prolonged skin contact with product or with contaminated equipment/surfaces. Do not get in eyes, on skin or on clothing.

Conditions for Safe Storage

Store in a closed container. Empty containers may contain hazardous residue. Store separately. Keep closed. Follow all precautions given on this safety data sheet. Protect from sunlight. Store in an area that is: well-ventilated, cool, dry. Store in an area that is: out of direct sunlight and away from heat and ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH® TLV®		OSHA PEL	
	TWA	STEL [C]	TWA	Ceiling
Toluene	20 ppm A4	Not established	Not established	Not established
Xylene (mixed isomers)	100 ppm A4	150 ppm A4	435 mg/m3	Not established
Acetone	500 ppm A4	750 ppm A4	1000 ppm	Not established
Methanol	200 ppm	250 ppm		
Ethylbenzene	20 ppm A3	Not established	100 ppm	Not established
Carbon dioxide	5000 ppm	Not established	Not established	Not established

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space

Product Identifier: Air Intake Cleaner

SDS No.: PLI-009

Date of Preparation: August 21, 2015

or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields.

Contact lenses should not be worn, they may contribute to the severity of the injury.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

The following materials should NOT be used: natural rubber, polyvinyl chloride, neoprene rubber. Suitable materials are: nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed. If the TLV is exceeded, a NIOSH -approved respirator is advised.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear yellow liquid.
Odour	Aromatic
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting)
Initial Boiling Point/Range	Not available
Flash Point	-5 °C (method not specified)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable aerosol
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.845 at 15 °C
Solubility	Negligible in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	< 1 centistokes (kinematic)
Other Information	
VOC %	75
Flame projection	> 100 cm no flashback
NFPA Classification	Aerosol, Level 3

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Stable at ambient temperatures and pressures.

Possibility of Hazardous Reactions

Product Identifier: Air Intake Cleaner
SDS No.: PLI-009
Date of Preparation: August 21, 2015

None known.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Carbon oxides. And other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Reports have associated repeated and prolonged occupational overexposure to various organic solvents with internal organ, brain and nervous system damage.

Likely Routes of Exposure

Inhalation.

Skin contact.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Toluene	7585 ppm (rat) (4-hour exposure)	5580 mg/kg (male rat)	12125 mg/kg (rabbit)
Xylene (mixed isomers)	6350 ppm (male rat) (4-hour exposure)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)
Acetone	30000 ppm (male rat) (4-hour exposure)	5800 mg/kg (female rat)	> 15800 mg/kg (rabbit)
Methanol	64000 ppm (rat) (4-hour exposure)	5628 mg/kg (rat)	15800 mg/kg
Hydrotreated, heavy naphthenic distillate	2180 mg/m ³ (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Hydrotreated light naphthenic distillate	2180 mg/m ³ (rat)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Ethylbenzene	~ 4000 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)

Skin Corrosion/Irritation

Moderate skin irritant.

Serious Eye Damage/Irritation

Moderate irritant.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Depression of the central nervous system, impaired vision and blindness. In some cases, there may be delayed effects on the nervous system.

High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and headache to unconsciousness.

Skin Absorption

No information was located.

Ingestion

Product Identifier: Air Intake Cleaner

SDS No.: PLI-009

Date of Preparation: August 21, 2015

If small amounts are swallowed not likely to cause injury. If large amounts are swallowed can cause effects as described for inhalation. Swallowing methanol may result in blindness or other eye damage and nervous system damage.

Aspiration Hazard

Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located for respiratory sensitization.

No information was located for skin sensitization.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Toluene	A4	Group 3	Not Listed	Not Listed
Xylene (mixed isomers)	A4	Group 3	Not Listed	Not Listed
Ethylbenzene	A3	Group 2B	Not Listed	Not Listed

Contains. (Ethylbenzene) which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans).

Key to Abbreviations

ACGIH® = American Conference of Governmental Industrial Hygienists. A3 = Animal carcinogen. A4 = Not classifiable as a human carcinogen.

IARC = International Agency for Research on Cancer. Group 2B = Possibly carcinogenic to humans. Group 3 = Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity

Development of Offspring

Contains a component that contains xylene, which is reported to be fetotoxic.

Toluene is fetotoxic based on animal studies.

No information was located for: Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

This product and its container must be disposed of as hazardous waste. Do NOT dump into any sewers, on the ground or into any body of water. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of in accordance with municipal, provincial/state or federal regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1950	Aerosols	2.1	---
IMDG (Marine)	UN1950	Aerosols	2.1	---
IATA (Air)	UN1950	Aerosols, flammable	2.1	---

Product Identifier: Air Intake Cleaner

SDS No.: PLI-009

Date of Preparation: August 21, 2015

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Emergency Response Guide No. 126 EmS F-D, S-U

Other Information ICAO/IATA PI Y203/203
Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are met.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

CEPA - National Pollutant Release Inventory (NPRI)

(Toluene) Part 1A.

(Xylene (mixed isomers)) Part 1A.

(Methanol) Part 5.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol)

California Proposition 65: Not applicable.

SARA Title III - Section 302: Not applicable.

SARA Title III - Section 313. (Toluene). (Xylene (mixed isomers)). (Methanol)

Massachusetts Right To Know: Not applicable.

New Jersey Right To Know. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol). (Carbon dioxide)

Pennsylvania Right To Know. (Toluene). (Xylene (mixed isomers)). (Acetone). (Methanol). (Carbon dioxide)

SECTION 16. OTHER INFORMATION

NFPA Rating **Health - 2** **Flammability - 3** **Instability - 0**

Based on Toluene

SDS Prepared By Regulatory Compliance

Phone No. 905.847.0222

Date of Preparation August 21, 2015

Key to Abbreviations ACGIH® = American Conference of Governmental Industrial Hygienists
CANUTEC = Canadian Transportation Emergency Centre
CAS = Chemical Abstract Services
CCOHS = Canadian Centre for Occupational Health & Safety
CNS = Central nervous system
GESTIS Substance Database
HSDB® = Hazardous Substances Data Bank
IARC = International Agency for Research on Cancer
ICAO = International Civil Aviation Organization
IMDG = International Maritime Dangerous Goods Code
LC = Lethal concentration
LD = Lethal dose
NFPA = National Fire Prevention Association
NTP = National Toxicology Program

Product Identifier: Air Intake Cleaner

SDS No.: PLI-009

Date of Preparation: August 21, 2015

OSHA = US Occupational Safety and Health Administration
PPM = Parts per million
STEL = Short term exposure limit
TDG = Transportation of Dangerous Goods Regulations (Canada)
TWA = Time weighted average

References

Material Safety Data Sheet from manufacturer.
CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).
HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS).
Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA (“BIOVIA”). Available from Canadian Centre for Occupational Health and Safety (CCOHS).
ECHA - European Chemical Agency, Classification and Labelling Inventory
GESTIS Substance Database
OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

Disclaimer

The information contained herein is offered only as a guide to the use and handling of this specific material and has been prepared in good faith. It is not intended to be all-inclusive, and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein.